





www.parinmedia.ir





MODEL	AS -4125GS-TNRT
СРИ	<ul> <li>Dual 4th Gen AMD EPYC<sup>™</sup> 9004 Series Processors</li> </ul>
GPU	<ul> <li>8x NVIDIA L40/ NVIDIA H100 80GB</li> </ul>
Memory	• 6TB DDR5-4800 in 24 DIMMs
Storage	<ul><li>4x 2.5" hot-swap NVMe SSDs</li></ul>
<b>Boot Drives</b>	<ul> <li>1x M.2 NVMe boot drive</li> </ul>
Networking	<ul> <li>Dual-port 10GbE NIC with</li> <li>1 AIOM/DCP 3.0 slot</li> </ul>

## **PRT4910NA2**



The new generation of AI server PR4910W is a 4U dual-socket rack-mounted accelerated computing server newly launched by Power leader Supercharged for the largest workloads with next



## **PRT2012NA2**

AMD platform 2U dual-socket server PR2012AM2 series, the call parameters are as follows: 1) Appearance: 2U rack type Disk: flo 2.5-inch/3.5-inch hot-swappable disks • All set break name low

## **PRT1280NA**



PR1280C is a 1U rack-mounted single-socket server based on the Intel Coffee Lake architecture, supporting one latest Intel Coresa Duo I3/Xeon E-2100 series processor; using DDR4ecc



## PRT2280NA

PR2280C is a 2U rack-mounted single-socket server based on Intel Coffee Lake architecture, supporting one latest Intel Core Duo I3/Xeon E-2100 series processor; using DDR4 ECC memory, which greatly improves the memory bandwidth



